Warranty & life time statement

aquatherm orange system aquatherm green pips aquatherm lilac pips bips system for recycled pipe system for recycled reclaimed water chilled and hot applications aquatherm system for chilled and hot applications and the pipe system for chilled a

aquatherm GmbH manufacture all pipes and fittings in accordance with the German DIN confirming a 50 year guarantee of service life in accordance with the permissible working pressure / temperature of their technical product manuals. Within the scope of this, aquatherm will supply replacement material pipe and fittings if damages are traceable to materials faults and defects.

Liability Warranty

furthermore within the scope of the aquatherm GmbH gives a 10 year guarantee which compensates for material damage to third persons, for investigation, removal, replacement, acceptance, dismounting or laying bare of all defective goods.

aquatherm Gmbh guarantee is conditional on:

- The fusion of joining of pipe and fittings using only aquatherm GmbH welding tools and devices.
- Installation of pipe and fittings are certified aquatherm installers and adherence to aquatherm GmbH technical rules and guidelines for correct installation principles.

Limits of Liability

•	For bodily injury	20.000.000 Euro
•	For property damage [per occurrence]	20.000.000 Euro
Installation Address:		
Description of Installa	ation:	
Name of Plumber:		
Signature:		
Date of Completion:		
Reg. Installer Numbe	r:	

This warranty must be fully completed, signed and returned with the completed test sheet within three months of the completion of the project installation to the New Zealand Agent.

aquatherm® NZ limited, P.O. Box 99 393, Newmarket, Auckland, New Zealand. Phone O9 5707204, Fax O9 570 7206

aquatherm NZ Test record - aquatherm green pipe installation principles

Description c	of the In	stallation	Preliminary Test
Street Address			[Testing procedure NZ January 2001]
Suburb			Test pressure - 20 bar:
City			1. Test pressure 20 bar 10 minutes.
			2. Unpressurise for 1 minute.
Type of Installation	Domestic		
	Commerci	al	3. Test pressure 20 bar 5 minutes.
			4. Unpressurise for 1 minute.
Type of Pipe	aquatherm		5. Test pressure 20 bar for 5 minutes.
	aquatherm	blue pipe	6. Unpressurise.
	aquatherm	lilac pipe	WARNING
	aquatherm	red pipe	
	aquatherm	grey pipe	It is imperative to have movement during test period. Tight clips or damaged pipes
	aquatherm or	ange system	in frame work will result in an incomplete
			test which will result in the warranty being invalid.
Time testing Started			
Time testing finished			Result preliminary test:
Test period (minutes)			The test is to be conducted as a continuous
Client:			test as 20 bar with the five steps noted above.
			The system MUST be pressurised THREE
Contractor:			TIMES with a minimum rest of one minute
			between re-pressurising.
Installers #:		Date:	
Declaration:			If leaking occurs, please replace the part and re start the testing procedure.
I declare that I have installed the above product in			The test is complete and acceptable when the
accordance with aquatherm specifications with no			above has been undertaken and no leaks are
branding mix			present.
Signature:			Finally, complete all parts for the test sheet and
			return a copy to:
aquatherm® NZ limited must recieve this information within 3 months of the installation for			aquatherm NZ Limited
the waranty to be valid. Please consult with your			P.O. Box 99393,
local area Council as the may require a copy of the			Newmarket ,
test results for the records.			Auckland 1149

www.aquatherm.co.nz. Phone: 09 570 7204 Fax: 09 570 7206